

## Declaration of performance according to Regulation (EU) 305/2011 Fireview 9kW - Free Standing Stove

|                      |  |  |   |
|----------------------|--|--|---|
| Point                |  |  | Woodwarm Stoves roomheater burning solid fuel without supply of hot water in accordance with BS EN 13240:2001 + Amd 2:2004  |
| 1                    | <b>Product Type</b>  |  |   |
| 2                    | <b>Product model designation</b>   |  | Fireview 9kW ,Serial No.-   |
| 3                    | <b>Intended use</b>  |  | Roomheater burning solid fuel without supply of hot water   |
| 4                    | <b>Manufactured by</b>   |  | Woodwarm Stoves Ltd.<br>Metal Developments Ltd, The Workshop, Wheatcroft Farm<br>Cullompton, Devon, EX15 1RA<br>Tel: 01884 35806 Fax: 01884 35505<br>Email: sales@woodwarmstoves.co.uk                        |
| 5                    | <b>Manufacturer's authorised representative</b>  |  | Woodwarm Stoves   |
| 6                    | <b>System of assessment and verification of constancy of performance</b>   |  | System 3  |
| 7                    | <b>Notified laboratory name and address</b>  |  | The notified laboratory Kiwa Gastec at CRE. Laboratory no. 692 performed the determination of the product type specification on the basis of type testing under system 3 and issued the test report Ref: 6282 |
| 8                    | <b>Declared performance:-</b>  |  |   |
|                      | <b>Harmonised Technical specification:</b>   | BS EN 13240:2001 + Amd 2:2004                |   |
|                      | <b>Essential characteristics</b>   | <b>Performance - Wood</b>                    | <b>Performance - Ancit</b>  |
|                      | Fire Safety:- Reaction to fire   | A1   |   |
|                      | Clearance distances to combustible materials   | Rear = 900mm<br>Sides = 450mm<br>Above = NPD |   |
|                      | Risk of burning fuel falling out   | PASS   |   |
|                      | Emission of combustion products  | CO = 0.55%                                   | CO = 0.26%  |
|                      | Surface temperatures   | PASS   | PASS  |
|                      | Electrical safety  | N/A  | N/A   |
|                      | Cleanability   | PASS   | PASS  |
|                      | Maximum operating pressure   | N/A  | N/A   |
|                      | Flue gas temperature at nominal heat output  | 289°C  | 260°C   |
|                      | Mechanical resistance to carry a chimney   | NPD  | NPD   |
|                      | Nominal output   | 9.1kW  | 9.3kW   |
|                      | Room heating output  | 9.1kW  | 9.3kW   |
| Water heating output | N/A  | N/A  |   |
| Gross efficiency     | 71.1%  | 72.8%  |   |
| Net efficiency       | 78.5%  | 74.7%  |   |
| 9                    | The performance of the product identified in points 1 and 2 is in conformity with the declared performance given in point 8. |  |   |

Signed for and on behalf of the manufacturer by:

Simon Brown

28 / 09 / 2015

SJBrown