

WILDWOOD 5kW PFT INTEG LOG STORE STYLE SLENDER CE APPROVED CLASS 1: BS EN 13240:2001 + Amd 12:2004 WOODBURNING STOVE. AVAILABLE WITH 3 BASE OPTIONS – STANDARD, F/V LEG STYLE AND INTEG LOG STORE STYLE.

Product Fiche

Commission Delegated Regulation (EU) 2015/1187

Energy Labelling of Local Space Heaters

Supplier`s Name or Trademark:	Woodwarm
Suppliers Model Identifier:	Wildwood 5kW
Energy Efficiency Class of Model:	A
Nominal Heat Output to Room (kW):	5
Nominal Heat Output to Water (kW):	n/a
Seasonal Space Efficiency (%):	69.1
Net Efficiency (%):	79.1

NOMINAL HEAT OUTPUT 5kW
EFFIENCY WOOD 79.1%

OVERALL STOVE DIMENSIONS.

HEIGHT– 779mm
 WIDTH – 505mm
 DEPTH – 302mm

DISTANCE FROM COMBUSTIBLES WITHOUT HEAT DEFLECTOR:-

TOP - 450 mm
 REAR - 700 mm
 SIDE - 450 mm
 FRONT – 300 mm

HEARTH - The stove is on minimum of 250mm log store so the hearth can be superimposed 12 mm deep and made of non-combustible material (glass, steel, concrete)

DISTANCE FROM COMBUSTIBLES WITH A HEATSHIELD (OUR OWN TESTING)

REAR FLUE ADAPTER CANNOT BE USED WITH A HEATSHIELD
 WITH ONE HEAT DEFLECTOR REAR CAN BE REDUCED TO – 350mm (HEAT0031SD1)
 WITH TWO HEAT DEFLECTORS REAR CAN BE REDUCED TO – 175mm (HEAT0031SD2)

FLUE 6" / 152 mm
 CENTRE OF TOP FLUE TO REAR OF STOVE – 131 mm
 HEIGHT TO CENTRE OF REAR FLUE 662 mm
 RFA - ADD 185 mm TO TOTAL DEPTH OF STOVE - CENTRE LINE OF RFA TO BACK PLATE OF STOVE 115 mm
 MAX LOG LENGTH 368 mm

FUEL IS NOT TO BE STORED UNDER OR AROUND ANY STOVE WHILE THE STOVE IS IN USE!

REGULATIONS AND INSTALLATIONS TO COMPLY WITH.

All local regulations, including those referring to national and European Standards (BS EN 15287-1:2007), Installation of chimneys and flues for domestic appliances burning solid fuel (including wood and peat) and BS 8303. Code of practice for installation of domestic heating and cooking appliances burning solid mineral fuel need to be complied with when installing this appliance.