

**WILDWOOD 9kW PROFILE FLAT TOP CE APPROVED CLASS 1: BS EN 13240:2001 + Amd 12:2004  
 WOODBURNING STOVE. AVAILABLE WITH 3 BASE OPTIONS – STANDARD, F/V LEG STYLE AND INTEG LOG  
 STORE STYLE.**

## Product Fiche

**Commission Delegated Regulation (EU) 2015/1187**

**Energy Labelling of Local Space Heaters**

<b>Supplier`s Name or Trademark:</b>	<b>Woodwarm</b>
<b>Suppliers Model Identifier:</b>	<b>Wildwood 9kW</b>
<b>Energy Efficiency Class of Model:</b>	<b>A</b>
<b>Nominal Heat Output to Room (kW):</b>	<b>9</b>
<b>Nominal Heat Output to Water (kW):</b>	<b>n/a</b>
<b>Seasonal Space Efficiency (%):</b>	<b>68.5</b>
<b>Net Efficiency (%):</b>	<b>78.5</b>

**NOMINAL HEAT OUTPUT**      9kW  
**EFFICIENCY WOOD**            78.5%

**OVERALL STOVE DIMENSIONS.**

HEIGHT ON 150mm STANDARD & F/V LEG BASE - 719mm  
 HEIGHT ON 250mm INTEG LOG STORE STYLE – 819mm  
 WIDTH OF PROFILE FLAT TOP - 595mm  
 WIDTH OF 150mm STANDARD & F/V LEG BASE – 650 mm  
 DEPTH OF PROFILE FLAT TOP 365mm  
 DEPTH OF 150mm STANDARD - & F/V LEG BASE - 460 mm

**DISTANCE FROM COMBUSTIBLES WITHOUT HEAT DEFLECTOR:-**

TOP - 450 mm  
 REAR - 900 mm  
 SIDE - 450 mm  
 FRONT - 300 mm  
 HEARTH – If the legs are shorter than 150mm the hearth needs to be a min of 125 mm (5") and made of solid construction (concrete, stone, brick)  
 If the stove is on minimum of 150mm legs, the hearth can be superimposed 12 mm deep and made of non-combustible material (glass, steel, concrete)

**DISTANCE FROM COMBUSTIBLES WITH A HEATSHIELD (OUR OWN TESTING)**

REAR FLUE ADAPTER CANNOT BE USED WITH A HEATSHIELD  
 WITH ONE HEATSHEILD, REAR DISTANCE CAN BE REDUCED TO – 450mm (HEAT0060SD1)  
 WITH TWO HEAT HEATSHEILDS, REAR DISTANCE CAN BE REDUCED TO – 225mm (HEAT0060SD2)

FLUE 6" / 152 mm  
 CENTRE OF TOP FLUE TO REAR OF STOVE – 151 mm + 45mm FOR LEG BASE PROTRUSION  
 HEIGHT TO CENTRE OF REAR FLUE 521 mm (621mm INTEG LOG)  
 RFA - ADD 185 mm FROM BACK PLATE OF STOVE - CENTRE LINE OF RFA TO BACK PLATE OF STOVE 115 mm  
 MAX LOG LENGTH 430 mm

**FUEL IS NOT TO BE STORED UNDER OR AROUND ANY STOVE WHILE THE STOVE IS IN USE!**

**REGULATIONS AND INSTALLATIONS TO COMPLY WITH:-**

All local regulations, including those referring to national and European Standards (BS EN 15287-1:2007), Installation of chimneys and flues for domestic appliances burning solid fuel (including wood and peat) and BS 8303. Code of practice for installation of domestic heating and cooking appliances burning solid mineral fuel need to be complied with when installing this appliance.